

Emergency Rescue Plan

Normal and auxiliary control systems built into a mobile elevated work platform (MEWP) will allow the operator to bring the platform of the machine safely to ground level under controlled conditions. It is extremely unusual not to be able to lower the platform using these controls or for all these systems to fail.

MEWP Details - Supplier / Manufacturer / Model / I.D.

| Locat | | |
|-------|--|--|
| | | |
| | | |

| Date and duration of rescue plan: FromTo | |
|--|--|
|--|--|

| Emergency Situation | Proposed Action | | |
|---|---|--|--|
| Failure of upper control functions while elevated | Where the normal upper control functions fail, the | | |
| | operator will use the upper auxiliary controls to lower the platform safely | | |
| Failure of the operator to be able to operate the | Where the operator is incapable of lowering the | | |
| MEWP functions while elevated due to one of the | raised platform using the upper controls, an | | |
| following reasons: | appointed person familiarised in the use of the | | |
| A. Operator incapacitated | "ground" controls will lower the platform safely | | |
| B. Auxiliary functions fail to operate from upper control station | using the normal ground controls | | |
| Failure of normal ground controls | Where the normal ground controls fail, an | | |
| | appointed person familiarised in the use of the "ground" controls will use the ground auxiliary | | |
| | controls to lower the platform | | |
| Failure of ALL normal and auxiliary lowering | Where all normal and auxiliary functions have | | |
| functions | failed, a competent and authorised service | | |
| | engineer should be contacted | | |
| | Name | | |
| | Name: | | |
| | Contact Details: | | |
| Names of nominated ground person(s) on site, familiarised and authorised to lower the work platform in the event of an emergency or a machine malfunction | | | |
| Name | Signature | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Union Bridge Works Roker Lane Pudsey Leeds West Yorkshire LS28 9LE

Tel: 0844 576 8375 Fax: 0844 576 8376 www.ich-services.co.uk

Consideration for mid-air rescue

A mid-air, platform to platform rescue should only be considered in exceptional circumstances and only after:

- All normal and auxiliary lowering procedures have been attempted and these are unable to lower the platform.
- Site management have contacted the competent and authorised service engineer listed in the rescue plan, to report failure of normal and auxiliary lowering systems and request engineering assistance.

If after inspection by the competent engineering assistance, it is not possible to affect a timely repair to allow the machine to be brought to the ground safely, senior site management should be contacted for permission to carry out a mid-air rescue.

Or

Where the competent engineering assistance is not readily available and an immediate risk exists to the health and safety of any of the occupants from remaining in the elevated basket until an engineer can attend, then senior management should be contacted for permission to carry out a mid-air rescue.

Code of Practice for Mid-air Rescue

- A. Rescue using another MEWP should only be performed once a site specific risk assessment has been carried out and a specific plan has been documented and approved by senior management.
- B. The rescue machine must be positioned so as to enable the rescue procedure to be carried out without comprising the safety of any personnel involved in the rescue procedure.
- C. The platforms of both machines must be adjacent to each other with a minimal gap between them, unless exceptional circumstances mean this is not possible. (Where this is not possible, the circumstances shall be recorded onto the risk assessment form.)
- D. Where reasonably practicable, precautions should be taken to prevent inadvertent movement of both platforms during the transfer.
- E. The person being rescued (transferred from basket to basket) should wear a full body harness with an adjustable lanyard the lanyard should be attached to the anchor point on the rescue machine before transfer takes place.
- F. Care must be taken not to overload the rescue machine during transfer. This may mean making more than one journey to complete the rescue.

Neil Blenkin

Managing Director

1st March 2019

